

CoroTap™ 200

Metrische Werte

ISO	MC-Code	ULDR	T200-SD	
			1.5	2
		HB	Vc (m/min)	
S	S1.0.U.AN	200	7	6
	S1.0.U.AG	280	5	4
	S2.0.Z.AN	250	7	6
	S2.0.Z.AG	350	2	2
	S2.0.Z.UT	275	5	4
	S2.0.C.NS	320	5	4
	S3.0.Z.AN	200	5	4
	S3.0.Z.AG	300	2	2
	S3.0.C.NS	320	2	2
	S4.1.Z.UT	200	7	6
	S4.2.Z.AN	320	7	6
	S4.3.Z.AN	330	5	4
	S4.3.Z.AG	375	5	4
	S4.4.Z.AN	330	5	4
	S4.4.Z.AG	410	5	4

Zoll-Werte

ISO	MC-Code	ULDR	T200-SD	
			1.5	2
		HB	Vc (feet/min)	
S	S1.0.U.AN	200	24	20
	S1.0.U.AG	280	16	13
	S2.0.Z.AN	250	24	20
	S2.0.Z.AG	350	8	7
	S2.0.Z.UT	275	16	13
	S2.0.C.NS	320	16	13
	S3.0.Z.AN	200	16	13
	S3.0.Z.AG	300	8	7
	S3.0.C.NS	320	8	7
	S4.1.Z.UT	200	24	20
	S4.2.Z.AN	320	24	20
	S4.3.Z.AN	330	16	13
	S4.3.Z.AG	375	16	13
	S4.4.Z.AN	330	16	13
	S4.4.Z.AG	410	16	13